



Distributed By GD DYNAMIC



## **Pan-Tilt IP Camera**

- •1.0 Megapixel ¼" CMOS Sensor 3.6MM Lens
- •Motion Alarm Trigger Record
- •Auto Email Snapshot & Video Record
- •Pan & Tilt Control horizontally 350°, vertically 90°
- •10Led light, 5M Infrared Lamp Range
- •H.264 Compression Format
- •Real time transmission up to 25FPS/1.0MP
- •Support PNP & Cloud Services
- •DC 5v power supply, Power consumption 1.5A
- •Support WiFi 802.11b/g & Ethernet RJ45 Network
- •Support Upto 16GB TF memory card
- •Onvif compliant

Item	Device	GD-EYEPT20WC
Viewing	1/4 inch CMOS	1.0 Megapixel CMOS Sensor
	Effective Pixels	1MP:1280*720 (HD)
Min.Scene Illumination	Color	0 LUX(IR ON)
	IR Sensitivity	yes
	IR Cut	Yes
Control	PAN & Tilt Control	Built-in Pan/Tilt Motor, horizontally 350°, vertically 90°
Lens	Lens	3.6MM
Day/Nigh	Infrared light	10 LED
	IR distance	5M
	Wireless	Support WiFi
Functions	Motion Detection	Yes
	Alarm Action	support email message etc
	AGC	Auto
	White Balance	Auto
Video Compression	Compression	H.264
	Picture Resolution	1MP:1280*720 (HD)
	Image Frame Rate	25fps
Casing	Accessories	Bracket, CD material, power, Screw bag
Alarm I/O	Alarm I/O	
Network	Ethernet	WIFI/RJ45 connector
	Protocol	HTTP/DHCP/IP/TCP/UDP/DDNS/HTTP/PPPOE/FTP/SMTP ; WIFI/ 802.11/b/g
Software	Web Browser	Above IE6
	Mobile Monitoring	Iphone ,Android, Symbian
	Remote	Built-in Web server, supports remote viewing and management;
	Browsing At The Same Time	Supports simultaneous browsing for up to 5 users .
Power	Voltage	5V
	Power Consumption	1A
Physical	Size	110*110*130cm L*W*H

Distributed By GD DYNAMIC